

ROOFS & ROOFLIGHTS · FIXED FLAT & WALK-ON ROOFLIGHTS

Flat Rooflights

Bring daylight deep into extensions and flat-roofed rooms with fixed flat rooflights in framed, frameless and walk-on versions, double or triple glazed with toughened safety glass.

0.7

U-value triple glazed (W/m²K)

5°

minimum fall

Walk-on

options available

Technical details

Types	Fixed framed · fixed frameless · walk-on rooflights · walk-on glass floors
Double glazed	6mm toughened outer + 6mm low-E toughened inner, argon, warm-edge super spacer · U-value 1.2 W/m ² K
Triple glazed	Toughened safety glass, argon, thermal super spacers · U-value 0.7 W/m ² K
Glass finishes	Clear low-E / solar clear · solar grey · satin privacy
Frame (framed)	Thermally broken aluminium, Anthracite Grey RAL 7016 or Black RAL 9005, other RALs on request
Border	Black RAL 9005 screen-printed border as standard, extended for upstands over 88.5mm
Standard sizes	300 × 300mm to 1000 × 3000mm framed, to 1000 × 2500mm frameless (internal opening) · bespoke on request
Installation	Onto a timber upstand at a minimum 5° fall, fixed from outside or inside
Walk-on	33mm triple heat-soaked toughened laminated glass · PAS 24-2016 and BS 6375 tested · clear, opaque or anti-slip
Standards	Glass to BS EN 12150 · units to BS EN 1279
Guarantee	10 years

Key benefits

- Framed, frameless and walk-on versions
- Double (U 1.2) or triple (U 0.7) glazing
- 6mm toughened safety glass inside and out
- Clear low-E, solar grey or satin privacy glass
- Grey or black thermally broken frame
- Standard and bespoke sizes

Ideal for

Flat-roof extensions · Kitchens & hallways · Bathrooms (privacy glass) · Roof terraces & basements (walk-on) · Garden rooms

Sizes are internal opening sizes, measured from the inside of the upstand. The frame covers a finished upstand up to 88.5mm wide; wider upstands need an extended border. Minimum fall 5°.

Talk to us about your project: we work from drawings, measure every opening on site, and fit with our own team.