SLIDING DOORS · CONCEALED-FRAME SLIDING DOOR

GLIDE21

When an opening is too big for anything else, GLIDE21 takes over. Panels up to 3 metres wide and 3 metres tall, a 21mm interlock and a fully concealed outer frame, so all you see is glass and handles.

21mm	3m × 3m	450kg
interlock sightline	maximum panel size	maximum panel weight

Technical details

Interlock sightline	21mm
Max sash size	3000 × 3000mm
Max sash weight	450kg
System depth	146mm dual track · 216mm triple track
Frame	Fully concealed outer frame, hidden sash
Glazing	Up to 32mm, wrap-around glazing
U-value	1.3 W/m²K double glazed
Threshold	Flush · 46.5mm frame threshold height · 81mm frame height
Meeting stile	100mm
Weather	Air Class 4 (600 Pa) · Water Class 9A (600 Pa) · Wind Class B5 (2000 Pa)
Options	Fixed and sliding panels · reinforced interlock · fixed or adjustable rollers · single and dual colours

Key benefits

- Panels up to 3m wide and 3m tall for the largest openings
- Fully concealed outer frame and hidden sash, with only the handles on show
- Slim 21mm interlock
- Panels up to 350kg as standard and 450kg with options
- Flush internal threshold as standard for level living
- High weather ratings including Class 9A water tightness

Ideal for

Very large openings · Luxury new builds · Level thresholds · Frameless look

Talk to us about your project: we work from drawings, measure every opening on site, and fit with our own team.

Manufacturer data. Performance varies with size, glass and configuration, and is confirmed at survey.